Amateur Radio

JOURNAL OF THE WIRELESS INSTITUTE: OF AUSTRALIA

For the Experimenter and Radio Enthusiast



plan right from the start There's a PHILIPS valve for every socket of every transmitter or receiver. Add to this the PHILIPS name for reliability and Specify unfailing quality as the reason why so men throughout the specify—PHILIPS.

PHILIPS VALVES unfailing quality and you have the reason why so many radio men throughout the world always

PHILIPS ELECTRICAL INDUSTRIES PTY. LTD. Sydney · Melbourne · Brisbane · Adelaide · Perth

THE BEST BY TEST FOR HIGH GAIN AND HIGH LEVEL AMPLIFICATION

"HAM" RADIO SUPPLIERS

5A Melville Street, Hawthorn, Victoria

North Balwyn Tram Passes Corner, near Vogue Theatre. Phone: WA 6465 over 10 lbs. in weight, 5/- extra.

Money Orders and Postat Notes payable North	mawmorn r.o. racking Charge	on an goods
Command Transmitters: Freq. 4—5.3 Mc., 5.3 —7 Mc., or 7—9 Mc. Complete with valves and crystal	NEW VALVES	Command R Command R As new, le
ATS Transmitter, complete with valves, £19 322 Transmitters, comp, with valves, £12/16/- ATS Aerial Tuning Units, A.W.A. Contains two Relays and 6-5 Ms. Meter £2/16/- Bendix RAIB Power Supplies, £10 with AC, 24v, at 1 amp, output 256v, HT, £5 each, Genemotor Power Supply, new, SCR322, 24v- input, 156v, and 256v, output at 360 Ms. Includer explay, voltage regulator, etc. A gift at 35/ Too heavy for postage. 23v, Filament Transformers	12K8 10/- 211 30/- 834, R.C.A. £1 884 Gas Triode 25/- 100TH 45/- 954 American 10/- 957 Acour Triode. Filament: 1.25v. at 50 Ma. plate current 2 Ma. ideal for current 2 Ma. ideal for 10/- EFS0 10/-	AR8 Receiv air-tested AR12 Receiv tains Xtal AR8 Connec 522 Receiver R1155A Eng five bands inal condil AR301 High one 955, si converted American L. less Gene
4v. Filament Transformers	TESTED VALVES EX DISPOSALS GEAR 1A3 10/- 6U7 10/-	Relays, A.V 12 volt American "Leach,"

25/-

16/-	6U7	10/-
10/-	6V6	10/-
7/6	6X5	10/-
7/6	7A6	10/-
7/6	7A8	10/-
10/-	7C5	10/-
10/-	7C7	10/-
10/-	7F7	10/-
10/-	7G7	10/-
10/-	7N7	10/-
		10/-
20/-	7¥4	10/-
12/6	12A6 .	10/-
10/-	12AH7	10/-
10/-	12C8	10/-
		10/-
		10/-
		10/-
12/6	12SQ7	10/-
10/-	12SR7	10/-
	807	10/-
		50/-
		50/-
10/-	815	50/-
10/-	832	50/-
10/-	866	20/-
5/-	95G	10/-
	1603	10/-
	1626	10/-
10/-	1629	10/-
	10/- 7/6 7/6 10/- 10/- 10/- 10/- 10/- 10/- 12/6 10/- 15/- 15/- 12/6 10/- 11/- 10/- 10/- 10/- 10/- 10/-	10/- 6V6 7/8 6X5 7/8 7A8 7/8 6X5 7/8 7A8 7/8 7A8 10/- 7C7 10/- 7C7 10/- 7C7 10/- 7C7 10/- 7C7 10/- 7C7 10/- 12/- 12/- 12/- 12/- 12/- 12/- 12/- 12

6K7G 7/6

6N7 ... 10/-

ENE 15/-9002 10/-

SR7 10/-

6SH7 5/-9994 10/-

6SK7 10/-OA4 10/-

6SL7 15/-VR105 15/-

6SN7 10/-

ESST 10/-

6SH7GT 4/-

68J7 .. 10/-

6L7 ... 10/- 1629 10/-

2051 __ 10/-

7193 ... 5/-

9001 ... 10/-

EF50 .. 7/6

VR150 15/-

VR65A 2/6

teceivers, 150-550 Kc., £9/10/eceivers 3 to 6 Mc and 6 to 9 Mc. ess genemotor; air tested, £7/10/vers, complete with Valves and £22/10/ver, converted to 230v. AC. con-

£27/10/-Filter ting Cables, 8-pin sockets, 5/- ea, s. original cond. with valves. £9 lish Com. Receiver, nine valves, fren, range: 25 Kc.-18 Mc. orig.

tion, less power supply, £29/10/-Freq. Receiver, uses three 954s, x 6AC7 I.F. stages at 30 Mc. Easily to 144 Mc. Complete £6/10/-F.F. Units, complete with Valves, motor £5 each V.A., Aerial Change-over type.

Antenna Change-over Relays 24 volt 250 ohms, ceramic insulation, Beautiful job. A gift at 35/-

Coils, small slug-tuned type, suitable for Converters, etc. 3/6 Shielded Wire, 16 a.w.g. single core. In 100 yard roll

English Carbon Mike Transformers, new, 5/-

LARGE S	STOCK OF	CRYSTA	LS
100 Kc. R.C.A	. Crystals		£
1,000 Kc. Crys valve socke	tal mounted i	in case with Continental	10-pir
Marker Cryst Crystals green on request,	als, 3.5 Mc., ound to any	Me., and frequegney.	10 Mc
Following is available for	a list of Cr	rystal Frequelivery, £2	encies
		Kc. 8176.5	923 Ke
			50 Kc
	00 Kc. 7100		5 Kc.
1777.5 Kc. 70	10 Kc. 7109	Kc. 8317.3	2 Kc.
2050 Kc. 70	12 Kc. 7118		
2075 Kc. 70 2716 Kc. 79	13 Kc. 7121	Kc. 8326	
		Kc. 8488	
3482.5 Re. 70		Kc. 8500	
3503 Kc. 70. 3509 Kc. 70.	22 Kc. 7130		
3511 Kc. 70			
	32 Kc. 7156		Mc.
	32.6 Ke. 7163		Mc.
3516 Ke. 70			6 Me.
			4 Me.
		3 Kc. 10.54	6 Mc.
3539.3 Kc. 70		Kc. 10.56	
		5 Kc. 11 M	
		Kc. 12.80.	3 Mc.
3675 Kc. 70		5 Kc. 14.02	
4285 Kc. 78			
4600 Kc. 70		71 Kc. 14.32	
5000 Kc. 70	93 Kc. 8171	250 Kc 14.32	

Amateur Radio, February, 1954

Valve Sockets, ceramic, 8-pin Octal ... Valve Sockets, ceramic, 4-pin ____ 2/6 Five-core Cable, not shielded 8d. yard Solor 28 pF. silver plated wide-spaced - 7/6 each Condensers 72 Ohm Co-axial Cable Co-ax Connectors, male/female, small Pi type, new 2/6 pair 2 uF. 1000v. block type Chanex Cond., 12/6 Shielded Cable with two 12-pin Plugs 7/6 Phone Plug and 4 ft. Cable, American .. 4/6 Meters-0-5 Ma., square type, new 27/6 Meters-0-5 Ma., 2" round, scale 0-15, 0-250 Ma., A.W.A. AT5 type, less ext. shunt, 25/-Meters-9-40, 9-120 Ma., separate connection.

WANTED URGENTLY, STATE PRICE.

American Headphones, low impedance, com

Single Shielded Hook-up Wire, new, 8d. yard Hammarlund BC191E Plug-in Coil Units, contains two variable condensers, coil formers. fixed condensers, etc. Complete £2/10/-. Less vernier dial, £2. Six volt bayonet type Dial Lamps 1/- each Locktal Sockets 1/6 each

plete with Cable

Meters-0-150 Ma., round type, new __ 27/6 Meters-0-20 volt, 5 Ma. movement, square type, 2 inch, new Meters-0-2.5 Amp. R.F., square type, 2 inch. new .

Meters-0-5 Ma., 13 Ma, movement, round type, 2 inch, new 22/6

WANTED TO BUY-RADIO PARTS, VALVES, TRANSFORMERS, RECEIVERS, TRANSMITTERS, ETC.

íi.

FEBRUARY - - 1954 Vol 22 No 2

EDITOR:

T. D. HOGAN, VK3HX, Telephone: UM 1732.

MANAGING EDITOR:

J. G. MARSLAND, VK3NY.

TECHNICAL EDITOR: J. C. DUNCAN, VK3VZ.

TECHNICAL STAFF:

A. K. HEAD, VK3AKZ. L. B. FISHER, VK3AFF.

COMPILATION:

R. W. HIGGINBOTHAM, VKSRN. K. E. PINCOTT, VK3AFJ.

CIRCULATION:

I. K. SEWELL, VK3IK. ADVERTISING REPRESENTATIVE:

BEATRICE TOUZEAU, 96 Collins St., Melbourne, C.1. Telephones: Cent. 3411, MB 2111.

PRINTERS:

"RICHMOND CHRONICLE." Shakespeare St., Richmond, E.1. Telephone: JB 2419.

MSS. and Magazine Correspondence should be forwarded to the Editor, "Amateur Radio," Law Court Cham-bers, 191 Queen St, Melbourne, C.1, on or before the 8th of each month.

Subscription rate in Australia is 12/- per annum, in advance (post paid) and A15/- in all other countries.

Wireless Institute of Australia (Victorian Division) Rooms' Phone Number is FJ 6997.

WI BROADCASTS

All Amateurs are arged to keep these frequencies clear during, and for a period of 15 minutes after, the official Brondensis

VESWI: Sundays, 1100 hours EST, 7145 and 2000 hours EST 50 and 144 Me. frequency checks available from VKS' Intrastate working frequency, 7125

VK4WI: Sundays, 0000 hours EST, sh ously on 3500 and 14343 Kc. : channel is used from 0015 hours hours each Sunday for the Country hook-up. No frequency

VK5WI: Sundays, 1000 hours SAST, on Tide Kc. Frequency checks are given by VKiMD and VK5WI by arrangements only on the 7 and 14 Mc. bands. VKSWI: Sundays, 0930 hours WAST, on 7148 Kc. No frequency checks available. VKIWI: Sundays, at 1000 hours EST, on 7146 Kc. and 146.5 Mc. No frequency checks are available.

AMATEUR RADIO

Published by the Wireless Institute of Australia. Law Court Chambers, 191 Queen Street, Melbourne, C.1.

EDITORIAL

WELCOME TO OUR ROYAL GUESTS



In common with all other citizens of Australia, we, the members of the Wireless Institute of Australia, humbly extend to our Royal Guests a hearty and sincere welcome to this "Our Land."

As this is the first occasion on which a reigning Queen has visited Australia, we are deeply appreciative of the honour bestowed upon us and look forward to the time when Aus-

tralia will become the second home of our Queen and her family, We pledge ourselves to do everything in our power to make this visit a happy and memorable event.

Taking a lead from the Motto of the Boy Scouts, we will hold our-selves prepared at all times to serve loyally.

"GOD SAVE THE QUEEN."

THE CONTENTS

Skeleton Slots 2	Trade Review-Eddystone "700"
Let's Listen 5	Communications Receiver 11
	Fifty Megacycles and Above 13
The Complete Amateur—The	20th A.R.R.L. International DX
V.F.O 6	Competition 13
Amateur Call Signs 7	DX Activity by VK3AHH 15
A Treatise on Practical Modern	Prediction Chart for Feb., 1954 15
Recording Tape 9	Federal, QSL, and Divisional
	Notes 16

SKELETON SLOTS

BY A. HAVYATT,* B.E., G3IFS/VK2AET

SLOT aerials were developed during World War II. for use at centriwavelengths in order to provide an efficient radiator for energy at those ultra high frequencies. were originated in wave-guide technique for radar, and with subsequent

development, have been used for v.h.f. broadcasting and other v.h.f. purposes. About three years ago the B.B.C. erected at Wrotham, England, a radiator for 90 Mc. f.m. transmission and this radiator is technically described as an assembly of co-phased slots on the surface of a vertical cylinder. This, in effect, consists of 32 slot radiators arranged in eight tiers with four in each tier spaced equally around the circumference of the vertical cylinder. In addition, it has been suggested that this form of radiator would be suitable for use in aircraft by cutting slots in the aircraft skin and plugging with the aircraft skin and plugging with dielectric, thus avoiding the use of projecting whit serials. A further suggested application is their use as marker and landing beacon radiators on aerodromes when they could radiate from horizontal slots let into the surface of the ground, even in the surface of a

runway if necessary. At centrimetric wavelengths, energy is transmitted more efficiently as bound-ed electromagnetic waves in a waveguide than as currents in a wave-guide than as currents in a conductor. When it is required to radiate the energy which is being carried by the wave-guide, it is not necessary to put the energy back into current form and then radiate from an aerial, but insteadelectromagnetic wave can radiated directly.

Fig. 1.-Demonstrating difficulty of construction array of dipoles at centrimetric wavelength Fig. 2.—Rediating slots equivalent to the array of dipoles in Fig. 1.

It is easy to understand that an array of dipoles (Fig. 1) would be difficult to construct in order to provide correct phasing and impedance matching at these frequencies so that some other form of radiator becomes desirable.

This problem is overcome by punching a row of holes in the side of a wavede so that each hole radiates some of the energy passing down the guide. It is, of course, necessary to make the holes of suitable length to act as radiators, and also to space them correctly

so that they are fed in uniform phase HOW A SLOT RADIATES You will no doubt be asking now how slots manage to act as radiators, 23 Archbold Road, Roseville, N.S.W.

and it is a little difficult to see what they have in common with other types of aerial. First of all, a slot in an infinite sheet is closely equivalent to a flat strip dipole in free space if it is assumed that the shapes of conductor and dielectric be interchanged. Refer-ence to Fig. 3 will make this analogy clear where it will be noted that the input impedance is approximately ohms in the case of the dipole and 500 ohms for the slot.



Fig. 3.—Dipole and corresponding slot in an infinite speet.

It is well known that the electric in the same direction as the dipole, i.e. horizontal polarisation is obtained from a horizontal dipole. And as the electric field is at right angles to the magnetic field, it follows that the magnetic field from a horizontal dipole will be ver-tical. Other well known facts that emerge in connection with the dipole are that it has maximum current at the centre and maximum voltage at the ends.

However, in the case of the slot, it can be seen that, viewed from the feed the slot edges form shortcircuited quarter wave transmission lines. This arrangement has a high input impedance, so that heavy currents will flow in the short-circuited ends and a high voltage will appear across the feed point, its value tapering off to-wards the short-circuited ends. This voltage across the slot lips forms an electromagnetic field in the slot which is free to radiate outwards from both sides of the sheet. The electric field is polarised in a plane at right angles to the slot length, i.e. horizontally, whilst the electro-magnetic field is vertical, assuming a vertical slot. The important point that emerges here is that the horizontal dipole and the vertical slot both produce horizontally polarised

The vertical electro-magnetic radiation, and hence horizontal electric field. could also be explained by the fact that current flows in the horizontal ends of slot causing radiation of energy, whilst currents flowing in the vertical sides flow in opposite directions and cancel each other out (Fig. 4).

Another point of great similarity between the slot and the dipole is that each can be folded to alter its input impedance. A folded dipole has its impedance increased fourfold, whilst the folded slot has its impedance reduced to a quarter of its original value, with a resultant construction as shown in Fig. 5.



Fig. 4.—Distribution of current in sheet sur-rounding slot radiator, Fig. 5 .- Folded slot.

FIELD STRENGTH PATTERNS

At this stage it would be as well to examine the field strength patterns of the slot aerial to enable a comparison to be made against the ordinary dipole. It will be seen (Fig. 6) that the horizontal pattern has a figure-of-eight shape similar to that which is obtained from a horizontal dipole, whereas the vertical pattern has higher energy radiavertical pattern has higher energy radia-tion parallel to the ground than at right angles to it. This latter pattern reveals the difference between the two aerials as the corresponding dipole pattern would show equal radiation in all directions It is immediately apparent that the

vertical radiation pattern is somewhat similar to that which would be obtained from two stacked dipoles, or a "one-over-one," and is therefore a very desirable feature for v.h.f. propagation. In addition, a conventional type of dipole reflector can now be added which gives this simple aerial a forward gain in excess of 4 db and having a broad frontal lobe.





--FIG 500

SIDE VIEW P 4107 SIG S(b)

Fig. 6 (a).-Horizontal radiation pattern. Fig. 5 (b) -Vertical radiation nattern.

PRACTICAL DESIGN So far the discussion has centred around slots cut in an infinite sheet

which is impracticable and still con-tinues to be so for sheets of finite size owing to high wind resistance and difficulty in arranging for rotation, not to mention being most unsightly. One way out of the difficulty is to use a construc-tion of wire netting, this in fact being quite permissible and resulting in a satisfactory aerial for certain applica-tions. But in experiments to determine how much of the sheet could be cut away to reduce unnecessary metal, it

(Fig. 2).

was found that satisfactory operation could still be achieved with quite a narrow band of metal provided the width of the slot was increased as the surround was decreased. This led to the construction of a radiator in small diameter tube and ultimately became known as the skeleton slot aerial. For successful operation it was found that the tube diameter should not be less

Owing to the fact that a point of minimum voltage appears at each end it is not necessary to employ insulators, and the aerial does in fact lend itself to all metal construction if this is desired. A slot aerial employing the Yagi method of construction is impracticable so that stacked construction must employed to obtain a smaller vertical angle of radiation, and dimensions for a two-stack skeleton slot suitable for use on two metres are given in Fig. 7.

Flat or circular twin feeder of 300 ohm impedance may be used to provide effective feeding and matching elements. When 300 ohm feeder is used elements. When you only leeder is used as phasing lines, it has a velocity factor of 0.82, so that if half wave lines are used, thus giving the same impedance at the feed end as the element impedance, they should be 33" long. Then, two such sections in parallel for the array illustrated will present an imped-ance of approximately 250 ohms, to which 300 ohm transmission line may be attached without serious mismatch If on the other hand it is desired to use 75 ohm co-axial transmission line, the phasing sections may be made threequarter wavelength long, i.e. 50", so



Fig. 7.—Dimensions of Two-Stack Two-Metre Skeleton Slot showing feeder connections.

that the feed point impedance becomes 90 ohms, to which 75 ohm co-ax transmission line may be attached again with permissible degree of mismatch. A better match may be obtained by using a Q-bar section which can be calculated to suit individual requirements.

There is no need to limit this array to two elements, as any number may be used provided arrangements are made to feed and match the sections correctly, and standard methods of doing this can be employed.

CONSTRUCTION

A satisfactory material for construction of the skeleton slot is is screwed conduit, but care should be exercised in bending the corners, for which a bending machine of the type used by elec-tricians is an advantage. Reflectors can be of the same material to provide uniformity of appearance.

It will be necessary to fit projecting pieces from the middle of each side of the slot towards the centre so that the phasing lines can be attached. They may be of a lighter material and 1" copper is suggested, as long as these projections are not expected to take too projections are not expected to take too much pull from the phasing lines. Alternatively, an extra length may be left on the half wave phasing sections so that they can be split down the middle and parted to make a connec-tion to each side.

CONCLUSION The skeleton slot aerial has not been

The sceneton sor aerial has not been developed to any great extent yet, although the slot aerial, from which it originated, is well established. Additional research and experimentation needs to be carried out so that keen v.h.f. workers should find plenty to interest them with this new aerial, BIBLIOGRAPHY

- "Slot Aerials and Their Relation to Com-plementary Wire Aerials (Babinet's Prin-ciple)," H. G. Booker, J.I.E.E. Vol. 93 Part III.A. p. 620.
- 485

THE HOUSE OF QUALITY PRODUCTS

HAM SPECIALS!

Type DLS-10 Vacuum Thermal Delay Switches-contact rating 250 volts at 6 amps. Protect those valuable mercury vapour rectifiers and associated equipment by limiting application of AC to the rectifier plates until the filaments are at operating temperature. Nominal heater voltages 2.5 to 6 volts gives delay of 30 seconds to 90 seconds. Price 12/6 each. Sockets to suit above rated 3,000 volts, 5/1. Postage extra

VALVES-Acorn Types 955 and 954 18/- each

CONDENSEES—U.C.C. high capacity 55 nF. 350 volt DC working Electrolytics. Negative and positive terminals isolated from can. Vertical mounting. 5/10 each. isolated from can.

AERIAL WIRE, 14 gauge hard drawn copper wire for all aerial installations. Cut to any length. 6d. yard.

BC-191-F 100 Watt Phone Transmitter, complete with remote control units RM-13-D and RM-122-D, 1,000 voit 300 Ma. automatic AC power supply, telephone handsets, interconnecting cables and instruction books. Brand new Price £185. Latest modifications available for use in exclusive Ham Bands

GELOSO SIGNAL SHIFTER UNITS The Ham's dream for a compact five-band rig.

Unit will supply better than 3.5 Ma. grid drive to a single 807 on all bands. Write for Brochure.

PRICE £10/4/9 (inc. Sales Tax)

Third large shipment almost sold now! Delivery due shortly. Place your order immediately and avoid disappointment.

GELOSO MICROPHONES

A beautiful range of Microphones and Microphone Inserts at attractive prices. Available from stock. Write for Technical Brochure and choose the unit-most suited to your requirements.

PLEASE INCLUDE FREIGHT AND POSTAGE WITH ORDERS

Established over 90 years.

& CO. PTY. LTD.

428 BOURKE STREET - MELBOURNE, C.1

Phone: MII 2426

TRADING CO.

319-321 SWANSTON STREET, MELBOURNE 393 FLINDERS STREET, MELBOURNE AND

96 OXFORD ST., SYDNEY

MAIL ORDERS WILL BE EXECUTED AT BOTH BRANCHES, PLEASE ADDRESS ALL MELBOURNE CORRESPONDENCE TO: P.O. BOX 5234, MELBOURNE

AT5/AR8 TRANSMITTING AND RECEIVING EQUIPMENT



AT5

£9/17/6

CONVERTED TRANSMITTER ARS RECEIVER

A high powered unit using two 807s from in final. Covering 140 Kc. to 20 Mc., with provision for six crystals and a

To operate direct 220-250 volt Output stage also altered to improve tone and re-Complete ception. with loud speaker in leatherette case. Price £34/17/8

JUNCTION BOX AND CABLES

Price £5

ARS RECEIVER

Il valve twin channel Receiver, using standard 6.3v. octal valves: six bands. Complete coverage 140 Kc. to 20 Mc £23/17/6



POWER SUPPLY, 12 or 24 volt

Price £10 TRANSMITTER-RECEIVER

AERIAL COUPLING UNITS Price £3/10/-

> BC459, 7 to 9.1 Mc., £7/10/-.

COMMAND MODULATOR

UNIT, Type BC456E In new condition, contains:

-24v. Relays

Price, £3/10/-COMMAND RECEIVER

1-12J5

-1625 -VR150/30

COMMAND RENDIX RECEIVERS

RADIO COMPASS Type BC453, 190 to 550 Kc., £12/10/--BC454, 3 to 6 Mc., £7/10/-. RECEIVERSI

BC455, 6 to 9.1 Mc., £7/10/-. 12v. input. Frequency range 200 to 410 Kc., 550 to 1200 Kc., and 2.9 to 6 Mc. Com-TRANSMITTERS plete with 12 valves and genemotor. Valve line-up: 4-8K7, 2-6N7, 1-6L7, 2-Type BC457, 4 to 5.3 Mc., £7/10/-. BC458, 5.3 to 7 Mc., 6J5, 2-6B8, 1-6F6, £7/10/-. £24/17/6

U.H.F. MIDGET HOMING RECEIVERS

range: 234-258 Mc. Can be operated from either 12 volt or 24 volt internal change-over switch. Valve line-up: 1-955, 3-954. Manually tuned dials calibrated in frequency. £4/19/6

MAGNAVOX

Two valve Interphone Ampliflers. Valves: 1-12A6. 1—12SL7. Complete with filter choke and output transformer.

£2/10/-

Type RT-34/APS-13 Frequency Modulated, approx. 450 Mc. Valve line-up:

9_6AG5 5-6,16 2-2D21 -VR105 Also contains Dynamotor, in-

put 27v. 1.5 amp., output 285v. 60 Ma. Price £17/10/-

GENEMOTORS

Type 72—Input: 27v. 3.6a., Output: 250v. 70 Ma., and 12.6v. 2.6 a., £1/19/6. Type DA-3A-Input: 28v. 10.5a., Output: 300v. 260 Ma., 150v. 10 Ma., 14.5v. 5a., £1/9/6.

Type 31-Input: 18v. 12s Output: 7.2v. 13a., 225v. 110 Ma., £1/19/6. TRANSMITTING TUNING UNITS by G.E.

VALVES BRAND NEW IN ORIGINAL CARTONS

1K7	10/6 VR150/30 22/6
6AC7	15/- 074
6B8	 15/- 001
6F6	12/6. 12A6 12/6
2051	22/6 2050, 22/6. This valve is
6K6G	12/6 suitable for use with Photo
6L7	12/6 Cell Relay Unit, as per June,
807	25/- 1953, issue of "Radio and
830B	60/- Hobbies."

CONTROLS, Type BC450 ASD RECEIVERS TYPE CPM-46A-BG -Slow Motion Dials. Single Pole Double Throw

Switches -Miniature Jacks. 3-Volume Controls, approx. 500 ohme

Price, £1/15/-Post, & Pack,: 6/-, Interstate 8/6.

V.H.F. RECEIVERS, approx. 300 Megs. Containing the following Valves:

6AC7	2-6V6G	1-6SJ7
-6H6	1-6SN7G	2-8X5G7
-2050	2-VR105/30	2-5U4G
-6A4G	1-VR150/30	2-2A3
	Price £17/10/-	

Type TU10B 10000 to 12500 Kc., £2/10/-Type TU7B 4500 to 6200 Kc., £2/16/-Type TU6B to 4500 Kc., £3/10/-

7700 to 10000 Kc., £2/10/-

BENDIX RADIO AZIMUTH CIRCLE LOOP AERIAL CONTROLS, Type MN22A Price 35/-.
Post. & Pack.: 4/9, Interstate 6/-.

LET'S LISTEN

BY C. A. CULLINAN.* VK7XW

Here is a simple c.w.-phone menitor which is r.f. driven. It operates over a wide frequency range without tuning and can also he used as an audio oscillator for code practice or tone work. The note is rich in harmonics which makes for easy listening. It's a small gadget of immense value in any station.

We all know that it is a very desirsignals and for phone work a simple diode operating a pair of headphones appears to be quite a favourite. However, when it comes to the matter of monitoring one's c.w. signals, the

problem is much more difficult Obviously the finest way is to devise some means of listening to the signal "off the air" with a high-quality device which will give a true reproduction. A sufficiently good, will show chirp and if sufficiently good, will show chirp and other faults very quickly. However, this ideal method has the great dis-advantage that the algon muscle advantage that the algon muscle device—this is time consuming and in these days of universal use of v.f.o's, is rapidly falling out of favour as are other methods which require tuning.

At the other end of the scale is the simple audio oscillator which is keyed simultaneously with the transmitter. This method is really simple, but does not give any clue as to what the actual

signal is doing. Whilst doing some work on the problem of telemetering for a b.c. station remote control system, it was realised that in a simpler form here was the answer to the problem of a c.w. monitor that lay in between the two extremes quoted. Then it was quickly seen that with a simple switching system a mon-itor could be built for either c.w. or phone operation as well as being useful as a code practice oscillator and a.f.

Basically the idea is to pass a sample of the carrier through a loaded rectifier and use the resultant positive voltage

to drive an audio oscillator. This then is the answer to the whole

problem and in practice it works to perfection, and in the completed instrument gives loudspeaker (or headphone if desired) monitoring of both c.w. and phone transmissions "off the air." Let's look at the circuit. A 6SN7 dual

triode valve is used as a combined diode audio oscillator, a 6V6 is employed as an audio amplifier, whilst a 6X5 provides the necessary d.c.

The r.f. circuit is untuned to get over te objections to tuned circuits. The grid and plate of one half of the 6SN7 are strapped together for diode operation, the cathode having a 0.5 megohm resistor shunted by a condenser of 0.00025 uF

The output of the diode is fed to a switch for c.w. or phone operation. The audio oscillator is a Hartley circuit using a push-pull output trans-former. The audio note is governed by * 64 Lawrence Vale Road, Launceston, Tasmania,

the values of C4, C5, C6, R2 and the

applied voltage.

Ouite a lot of experimenting can be done with these components to get a suitable note. However, it must be borne in mind that an oscillator of this kind is very rich in harmonics.

The output of the oscillator goes to a 6V6 audio amplifier by means of a second section of the c.w.-phone switch. In phone work the oscillator is disdemodulated output of the diode is passed to the audio amplifier.

In order to key the oscillator for use as a code practice unit, a jack of the type shown is connected to key in the cathode of the oscillator. This jack also removes the diode from the circuit and substitutes B plus voltage from a volt-

With a 5" loudspeaker, the unit will provide ample volume for any average

room for c.w. practice In our case, the whole unit was built into a small metal box and counling is made into the transmitter with a small coil at the end of a piece of co-ax cable. Care must be taken to ensure that the one's own transmitter. If it is used near a b.c. or other station, there may be a background of this station, but some shielding and a little care will take care of this except for those who operate in the immediate vicinity of such a station. For them, the input should be tuned

In the absence of a signal there will be a small residual current flowing in the diode load resistor and although the resulting voltage is very low it could cause the oscillator to operate very weakly. This would give the impression of a back wave. In this design it has been overcome by applying a small negative voltage to the diode via resistor R6. Be careful to note the con-

nections to the electrolytic condenser C9. Alternatively, a crystal diode, cor-rectly connected may be used in place of the half 6SN7, in which case any medium mu triode may be used for the oscillator In use the unit should be used with


just enough coupling to produce a good note with an unmodulated carrier. In phone work the volume will be less than that for c.w. for the same input and volume settings.

The condenser C4 (0.1 uF.) should

not be changed as with this value the unit should key satisfactorily up to at least 40 wp.m. There may be a slight chirp due to the fact that the oscillator is being keyed (either directly or inis being keyed (either directly or in-directly) and for this reason the trans-mitter keying should be checked from time to time by other means.

If you should go on phône after a c.w. session and the output of the mon-itor is garbled, you will probably find that the switch is in the c.w. position

oscillator is operating on and modulation.



C1--0.00025 uF. mica. C2. C3. Ct--0.1 uF. 200v. tmbular. C5-0.003 uP. mice. C5-0.01 uF. mice or tubular. C7-0.05 uF, 200v, tubular, CR_25 nF. Shy, electrolytic. C9, C18, C11—8 uF. 525v. elec-

R1-05 R2-01 R3-250 ohm 3w. 1 R4-0.2 megohm 1w. R5-30,000 ohm 1w. R6-25 ohm 3w. w.w. R7-0.5 megohm volume RFC-25 mH. R.F. Choke-

Power Transformer; primary to sull mains voltage, secondary h.t. 300-0 300 at 40 Ma., Lt. 6.5v, at 2 amp. 72 Push-pull output transformer, 10,000 ohms c.t. (secondary not used). CHI, CH2 Low resistance filter chokes Sundries—Two Jacks as shown, one wafer switch as shown, one loudspeaker to match \$V\$ valve.

THE COMPLETE AMATEUR

BY TOM ATHEY,* A.I.R.E.

PRIST as to the requirements of a complete station. The rules and complete station are rules and repair to the control of the

This leaves the more technical aspect and it is this that it is proposed to discuss. Each portion of a transmitter will be described, and circuits have been drawn, giving a basis upon year a constant of the control o

Many times during the course of lectures at the Queensland Division of the W.L.A.S. A.O.C.Y. Classes, the question arose just what gear was required that a chap may become an Amateur, revviding that he has his licence.

Consequently, as a past instrutor, the author has decided to the control of the control of the control of the construction of a complete Amaieur Station, capable of satisfying the most fastistious of intending Amateurs. The othics of the sport, and it is a sport, he leaves to the instructors, as well as the general theory, knowing full well that this side will be adequately covered.

Further, the author has always been an advocate of relay rack construction. Consequently, the whole rig is designed around a relay rack. This will give the rig a smart and professional appearance It is as well to note here and now that the aerial tuning unit is not included in the rack. This is to assist in harmonic reduction. Keep your aerial tuning unit as far away from the rack as practicable. And so to our first description—

SECTION ONE


THE V.F.O.

Rack Panel measurements—19" x 4 units Chassis not more than 17" x 8" x 2" deep

The circuit consists of the familiar electron coupled Clapp oscillator, followed by an isolator-buffer and then by a buffer-doubler to 80 metres.

The 6AG7 is undoubtedly the best caciliator valve available, as harmonics can be taken from it down to the fifth with ease. The mu is high—in the vicinity of 11,069—and if possible this type should be adhered to. However, if it is unprocurable use a 6M5 or 6BW6 in that order.

The fundamental frequency decided upon was 160 metres or 1750 Kc. As the band width is 3.5 to 3.8 Mc. on the 80



The whole unit is more elaborate than seem necessary. But to make a really good job of a transmitter, it is necessary to incorporate everything that will provide flexibility of movement, tidness or the state of the seem of

- movement:
- A crystal oscillator;
 Doublers and/or triplers to all bands through 80 to 10 metres;
- 4. Provision for manual keying; 5. Provision for modulation; 6. Ease of antenna coupling; and 7. A minimum of switching.
- *Ex-Instructor Qld. Division W.I.A. Classes; 41 Mountford St., New Farm, Brisbane,

and Joy in his work. Too many rigs in the past have been "haywired" inda although astounding results have been procured, even the owners admit tit tit could be cleaned up if they had the time. So chaps, when you begin you rig, begin it the right way—clean and neat.

It is proposed to deal with each portion of the transmitter separately and each circuit will, naturally, be included in the text. On each circuit all terminations are brought out to a panel to represent the rear of the chassis under discussion. Later on a complete diagram of cabling, interlacing all panel and chassis will be presented so that no error in cabling can be made. metre band, this means the variation must be 1780 to 1900 Kc. Allowing for a small overlap at each end, the tuning assembly must cover 1700 to 1850 Kc. The use of this low frequency for ceiver working in the vicinity of 1800 Kc. and note how much drift from frequency is there—34 sny—and no great care taken! So use a low frequency for well cover this same.

It is necessary to use high grade condensers in this unit. Double bearing shafted condensers preferably are best. In fact, it is recommended that the unit from the TU10 Tuning Unit be used. Looking at the circuit, Cl is your main fuming condenser. C2 is a negative

co-efficient condenser of 10 pF. capacity. Here you can use a Ducon N.P.O. type B ceramicon. C3 is a 5-25 pF. ceramic trimmer and again is a Ducon TS2A type N600 5-30 pF. trimmer. C5 and C6 have a capacity of 0.0015 uF. and must be silver mica. Use Ducon type SS even if the right capacity must be built up, Of course if other brands are available use them by all means. It just so happens that these types were available. The above values are critical so try and adhere to the values whereever possible.

The r.f.c. has an inductance of 2.5 H. All coupling condensers between the isolator and oscillator, buffer and isolator, and the coupler to the output should be mica. All by-pass condensers

can be of paper and tubular construction.

When wiring, use rigid lines for all grid wiring of the oscillator. Wire of a gauge about 14 s.w.g. or b. and s. tinned is good and will form a rigid

Chassis layout is left to each con-structor's choice. However, it is just as well to keep the grid circuit shielded from the plate circuit. This can be done by enclosing the grid components in a shielded box above the chassis and connect the plate wiring beneath it. In fact, it may be wise even to keep the coil and condenser shielded away from the valve and then enclose the whole in another shield. This will materially assist in stopping drafts from affecting the temperature and causing variation to frequency.

As the isolator's job is not only to disassociate any voltage variations be-tween the oscillator stage and the succeeding amplifiers, but is also to act as a builder of voltage, any high-gain pentode with a high slope will act here. It is an untuned stage and is capacity coupled to the buffer-doubler, which is a power amplifier.



H's the Super-Tropical capacitier made in withstend streams temperature variations from —40°C. to —10°C. Check these big fast area is Selid foil and paper assembly, non-second streams of the second stream of the second streams of the second s

Approved to Inter-Services Specification



The output of the buffer-doubler is tuned to broad-band characteristics by the small trimmer across the coil, and in turn is fed to the multiplier chassis through a mica coupling condenser of

A small power pack is required, rating about 60-80 Ma, at 250 to 285 volts each side of centre tap. The h.t., after filter ing, should be about 270v. Two tubes are used for voltage stabilisation -a VR105/30 followed by a VR150/30 in series. Thus the voltage to the oscillator plate is held at 255 volts, but the screen is held at 150 volts constant. It may be necessary to put a dropping resistor between the VR tubes and the h.t. supply, further isolating the oscil-lator from the normal h.t. feed.

After switching the unit on and allowing the unit to reach a steady operating temperature, no drift in frequency should be apparent if great care has been designed to remain on during the entire transmission and only the master switch controls it. When the master switch (to be shown later) is put on it cuts in the v.f.o. and all filaments of each portion of the transmitter. A final word on construction. A good dial is a must. One giving a high vernier action is most desirable, or the individual can devise some way to obtain an open reading that, at a future date, can be logged for future reference to assist in calibration.

If care is taken, the unit can be tuned by the one control and give fairly even output across the whole range of its

Incidentally, there is sufficient output from the buffer-doubler to enable it to act as a small low-powered c.w. rig on this unit working, you can get "on the air toot sweet."

AMATEUR CALL SIGNS FOR MONTH OF NOVEMBER, 1952 ADDITIONS

VK—S. W. Grimsley, Charles St., Tweed Heads, IAQN—J. F. Cox., Station: 3 New England Drive, Kingsgrove; Postal: 33 Oatley Rd.

Der Schwer geweine 2. Febru Englisch Professioner 2. Stein Profess

4LE-L. H. Cog. Nulgrove, Cooper Line, via Toowoomba. 4TC-A. Tremayne, 22 Quarry Street (Aero-glen.), Crims.

gien.), Ceirus, Australia 50N-C. J. Others, P. Holden, St., Hindmarsh, Westers Australia 65J-S. J. Smilb, 430 Great Eastern Highway, Midized Tassaniat TKM-K. G. McCrachen, 153 Bathurst St., Billiat.

Territories

IDY-G. E. Delahoy, Reard Island.

IEG-W. J. Storer, Australian Antarctic Con-

ALTERATIONS VE— New Seath Wales
2CS—Ocean View Parade, Charlestown.
3DW—32 Dargan Street, Yagoona.
2JI—89 Milson Road, Cremerue.
2QL—20 Abbotaferd Road, Homebush.
2QM—185 Darley Street, Mona Vals. IKQ 30 Crebert Street, Mayfield East, 2KB-66 Filinders Street, Crossilla. 2ABQ-311 Barrom Ayeune, Derlinghurst. 2AIT-22 Crane Road, Casile Hill, Sydney, 2AVP-Station 48 Kennedy St, Kingston, A.C.T. Postal: Reid House, Canberra, A.C.T.

Postal: Redd House, Carberry, A.C.T.

Postal: Bend House, Carberry, A.C.T.

27— Marrie Bend, Capitalded, Carberry, A.C.T.

28— Marrie Bend, Capitalded, Carberry, and York Terrett, Gotth Reference, Gotth Reference, Carberry, C. C. Carberry, C. Carberry, C. C. Carberry, C. Car

Western

AS—Carnemah

SEF—29 Lynion Street, Swanbourne.

SEW—28 Brighton Road, West Leederville.

Tasmania 74G—Swansea, 7MR—Stowport 7PM—C/o, 7NT Private Bag, Kelso.

DELETIONS

New South Wales: VKs 2EG (now operating under VK1EG), 3OK (now operating under New Statistics, 30% under VRIEGS, 30% under VRIEGS, 30% use new entry in vRIEGS, 3ADZ now operating under vRIDY, 3AFB, 3ARG, 3ASG (now operating under VRIPK), 3AFB, 3AKG, 100% operating under VRIPKE, 3AWW (now operating under VRIPKE, 1953)

FOR MONTH OF DECEMBER, 1953 ADDITIONS

VK.— New South Wales
2AQJ.—K. B. Pounsett, No. 38(T) Squadron,
R.A.A.F., Richmond.
2ARD.—R. J. Smith, Old Bethurst Road, Emu
Plains.

Palina. Victoria

AND.—N. T. Buchsann, 230 Ascot Vale Road,
Ascot Vale.

Ascot Vale.

Station: SSH. Lake Bags

Road, Bwan Bill: Postal: 288 Campbell

Street, Swan Bill:

Ballians.

Ballians.

Ballians.

Ballarai. Queensland
4FU-Dr. J. K. Fullagar, Medical Superintanders's Residence, Rockhampton Hospital,
Rockhampton.
1AC-A. C. Hawker, Macquarie Island.
1PG-J. H. Gore, Heard Island.

ALTERATIONS

VE— New South Wales 2CE-11 Wilkinson Lane, Dundse, 2EL-17 Cliedall Avenue, Canterbury, 2MZ-Fist 3, 27 Hawkesbury Rd, Springwood, 2AAF-Beaumont Road, Mt. Kuring-gal,

ZAAF—BESUMOON HOM, MI. KAURIG-261.

ZEE—11 Correa Avenius, Choltenham, S.E.
ZMI.—384 Ginnferris Road, Malvers, S.E.A.
ZMII.—45 KAURIG-261.

ZMII.—45 KAURIG-261.

ZMII.—45 KAURIG-261.

ZMII.—45 KAURIG-261.

ZMII.—45 KAURIG-261.

ZMII.—45 KAURIG-261.

ZMIII.—45 KAURIG-261.

ZM

AWB-92 Diamond Sireck, East Freeton.

(Re-115 Encyl Queensland,

(HM-95 Hunter Sireck, 1 Woolcown, N. 2.

(HK-95 Hunter)

DELETIONS

New Seath Wales: VRS 2NV, 2PG (now operating under VKIPC), 2ZZ, 2ABY, 2AEC, Victoria: VKS 2ET, 3IB (now operating under VKIAC), 3SJ, 3ABP (now operating under VKIAC), 3SJ, 3ABP (now operating under VKIAC), 3SJ, 3CB (Now operating under VKIAC), VKSAVK), (now operating under VKIAC), SVL (now operating under VKIAC), SVL

Page 7

MODEL "IXA" CRYSTAL MICROPHONE INSERT



AUSTRALIAN MADE - -FOR AUSTRALIAN CONDITIONS







FITTED WITH PLATED REAR SHIELD TO ELIMINATE HUM PICK-UP

- Patented crystal unit guarantees outstanding efficiency and performance,
- Protected against ingress of moisture with approved moisture sealed crystal element.
- Small compact lightweight durable. · Will not blast from close speaking,
- · Precision engineering ensures realistic reproduction and high output with long life and dependable operation.
- · The only unit available with a genuine sintered metal filter.
- Good high frequency response ensures excellent speech reproduction.
- Aluminium diaphragm mechanically protected
- and frequency controlled by "Zephyrfil" filter. Australian made throughout.
- · Only carefully selected cements used throughout, to suit Australian climatic conditions.

TECHNICAL DETAILS

Rochelle salt crystal microphones are perhaps the most widely used for all types of service where quality speech and music reproduction at high output levels is a requirement. They are dependable in performance and when fitted with the appropriate "Zephyrfil" filter, their frequency response may be adjusted to suit any application or requirement. This crystal microphone requires to be terminated with

a high value parallel load of the order of 1 to 5 megohms for best results.

The mass of the moving parts is small, hence the sensitivity is high and a high efficiency is achieved. Light gauge solder lugs are provided so that excessive heat in soldering will not be transmitted to the crystal element.

When mounted in a microphone cage, it is recommended that the insert be suspended in rubber, to eliminate shock and vibration.

One of the connecting lugs is directly connected to the case and care should be taken to solder the metal shield of the microphone cable to this solder lug, keeping the unscreened portion of the centre conductor as short as possible to eliminate hum pick-up.

All crystal elements are mounted on high grade suspen-sion pillars being fixed thereto with a good quality cement, thus ensuring stability and long life.

Case 1½" diameter (rear), ∦" thickness, 1-13/16" overall diameter (front) with filter fitted.

Frequency Response = 60-6,500 c.p.s. Output Level = -45 db (0 db = 1 volt/dyne/cm⁴) Impedance = Model 1XA Grid 1 -5 megohms.



Approximate Frequency Response Curve

AVAILABLE FROM ALL LEADING TRADE HOUSES

ZEPHYR PRODUCTS PTY. LTD. 118 WATTLETREE RD., ARMADALE, VICTORIA

A TREATISE ON PRACTICAL MODERN RECORDING TAPE

PART ONE

BY G. W. STEANE

MUCII has been written of late as to the advantages of tape against un to the advantages of tape against now it seems quite clear that tape has won the day as is evident by the almost word the advantage of the

Those of us who have used a wire recorder in the home have almost certainly been faced with the ordes! of joining the wire when it breaks—wire less than 4,000th of an inch thick or about the same size as a human hair—and mybe the same size as a human hair—and mybe the same size as a human hair—and in the machine wire which has caught in the machine itself.

Travelling at a relatively high speed,

usually more than 18" per second, which is essential for the reproduction of the higher frequencies, it is quite a mechanical problem to wind the wire evenly on to the spools provided and although the stainless steel wire now used is fairly strong, it is so easy to break same with "birds nests" or wire curlage all over the place.

Even on the best machine, there is no way of avoiding the background noise due to the rotation of the wire which invariably takes place.

One turn of record wire touching the next on the spools tends to leave an existence of the spools tends to leave an exilted "printing" or "echo" and so high can the background be that our leading broadcasting stations no longer use these recorders but have installed professional tape recorders instead.

Present day tapes consist of a noningentle base which supplies the necmagnetic base which supplies the neccoating which supplies the magnetic
terror of the supplies of the supplies
that the supplies of the supplies
that the supplies of the supplies
that the supplies of the supplies
to monothness. By using the proper
paper construction, a month frame of the
terror of the supplies
to supplies the supplies
to supplie the supplies
to supplies
the supplies
that the sup

Plastic base uses 0.0015 inch thick cellulose scetate. This is an improvement over the German practice, which used an oriented (stretched) vinyl material that would tend to wrinkle and shrivel up if overheated. This could easily happen in the back of a closed car in the summer sun. Plastic base is

It's nice to hear from Genf Stane after so many years. He was one of the original members was one of the original members WilAs going back to the spark days when we had the spark days when we had the spark that the spark of the spark successful to the spark successful to the spark successful to the spark walves, but he originally started the WIAA AO.CP. construction classes as theoretical instruction classes as theoretical instruction classes as theoretical instruction classes as the spark walves, but he originally started the WIAA AO.CP. construction classes as theoretical instruction that the Sydney University and in the measurine has been importwhich accounts for his extraordinary interest in this line.

much smoother and somewhat more uniform in thickness than is paper base. Hence the resulting tape has less background noise, less modulation noise, and lower distortion.

Black oxide has a higher coercivity than red and in the French tape it can show up to 320 oersteds, whereas red tape ranges around 280 oersteds.

Black oxide is recommended for tape speeds of under 'ii' per/sec. and will operate successfully on speech with tape speeds as low as 'ii' per/sec.

Continental tape manufacturers differentiate on red and black in this way whereas the Americans seem to use red tape for all speeds.

Black tape is, of course, harder to erase than red and the improvement in high frequency response is not apparent apart from any highly specialised applications.

The binder is a tough, flexible combination of synthetic restins, used to hold the oxide to the base. Since tape may be stored tightly wound on reels may be stored tightly wound on reside to the next. At the same time, the to the next. At the same time, the binder must not be made so hard that the tape is made stiff—for then it would not seat well on the heads, and the high frequency response would be impaired.

The coefficient of friction between the binder and metal must be low, otherwise the tape will not move smoothly over the heads—leading to flutter and to squeal. This must be achieved in the material itself; and not by applying a rub off and foul the heads and sometimes the capsian. The anti-friction quality must be an integral part of the formula.

Just to make the problem of the formulator more difficult, all these properties must be achieved without injury to the toughness and strength of

the binder, and without causing it to curl. A weak binder will rub off onto the heads very rapidly. Tape which has curled will not lie flat on the heads without excessive tension, and the high frequency response will be impaired.

For uniform quality from one foot of tape to the next, the oxide and the bunder must be completely mixed—an operation known as dispersion. The operation known as dispersion. The many hours in large mills, each welsh-many more than an automobile. Foor soite, as well as impair uniformity. The soite is a well as impair uniformity to the mills according to a carefully described and the soil of t

Modern laps has a ferrit-crotic custing on one side of either plastic or
paper base. This coating is made very
ing on one side of either plastic or
paper base. This coating is made via
f in width, which gives a tensile
strength of about 5 lbs. which is more
powers tape recorder. It is much assile
to drive tape at an exact speed and
forwards as in a wire recorder.

The side of the plastic strength of the plastic side of
forwards as in a wire recorder. We
still strength of the plastic side of the plastic side of
which saws it guide a problem to produce
a wire head which will, stand up to the
which saws its way through the softer
pole-plees of same, whereas in the case
a pressure of one on a crost the gap of
the head is sufficient to prevent flutter
and the wear of the head and tape is

Several types of magnetic tape have appeared on the Australian market of late months, each with their own technical characteristics and for the consideration of the construction of the c

However, on account of dollar restrictions, American tape is now off the market with the exception of a few market with the exception of a few readers to note that one of the leading manufacturers of tape recorders in USA. openly advertise that their tape USA. openly advertise that their tape the output drops 5 per cent which, in stell, gives our readers some dies of the durability of tape gentlements of the durability of tape gentlements of the durability of tape gentlements of the tape is lifted free from the magnetic head on called the control of the c

(Continued next issue)

ANTARCTICA

A ND this is the day! Long months of preparations, thousands of hours numerous proliminary tests, careful planting of instrumentation and research are over Melbourne, the 4th of Minister for External Affairs, Mr. Cassy, a last hand-shake, and the Kista Dan, the Danish exploration ship chartered provides the control of t

the seventh continent—Antarctica.

Aboard is a team of well-chosen men

Aboard is a team of well-chosen men

Australian sector of that vast, wide-open
land down south Bendes permanelly
planting the Australian Eag there on icy
ground, this means that actentific data
of great importance will, in future, be

available for the benefit of Australia, of
generational generat, in fact of future

generational

Let us recall that the whole continent covers an area of approximately 5,000,000 square miles.

5,000,000 square miles.

The children of the control of the contro

The climate of the colossal block of ice is rather unfriendly. Extreme values of air temperature are —18°F, and +32°F. The yearly mean temperature is approximately +12°F. Terrific snow-storms and gales are likely to blow any time during the year. Sunshine is a rarity.

Long is the chain of south-polar expeditions beginning with Capt. James Cook in 1774. To mention the Capt. James Cook in 1774. To mention Section 1974. To mention the Capt. James Cook in 1974. To mention 1987. Size futber William 1928. Size futber William 1928. Size futber William 1928. Size futber William 1928. Size futber 1974. Size futber in 1987. Size futber i

tribution to Antarctic research.

Almost half of the wide area
(2,472,000 square miles) is Australian
(2,472,000 square miles) is Australian
(2,472,000 square miles) is Australian
(2,472,000 square miles) is the place the
polymorphism of the square square
(2,472,000 square miles) is the place the
polymorphism of the square
(2,472,000 square) is the place the
polymorphism in 1,025. He named the land
after MacPherson Robertson who had
helped to finance his trip. Although the
main object of the square square
for the square square
(2,472,000 square) is the square
for the square square
(3,472,000 square) is the square
for the square
(4,472,000 square) is the square
for the square
(4,472,000 square) is the square
(4,472,000 square) is the square
(4,472,000 square

1947/48), have also been a major con-

includes work in meteorology, geology, surveying, biology, and geophysics. It is obvious that both official and Ham Radio comminication bock to this country and with other parts of the world will supply data which should be of will supply data which should be of the ten men undertaking this work on the cold continent are a literally handpicked team of experienced explorers, most of them Antarctic or sub-Antarctic

Leader of the expedition, as well as its surveyor, is Robert Dovers; others are the French observer Georges Schwartz, technical supermitendent and senior wireless operator L. E. Macey, metacorologist V. J. R. Dinge, geologist B. Stinnear, engineer John Russel, wireless operator and postmaster Bill Storer (YKIEGG), carpenter W. Harvey, and cook J. G. Gleadell.

BY HANS J. ALBRECHT, VESAHE

MAND E.

Boss Instituted
Bos. 1). 1947

BIN MACGORAER S.

AMTACCIC
STATION

C. March 15, 1946

Region of Australian Antarctic Research. (Southern Magnetic Pole at 71° 10' S. and 150° 45' E.)

The expedition camp will consist of several huts, their construction and outfit being the result of numerous experint theing the result of numerous experior long-time experiences of other explorations. Some of these huts are of a predatriculed type specially designed to be set up in MacRobertson Land will provide the necessary accommodation for men and apparettus and is intended to the supplied by two diesel electric hinterland. The camp's electric power will be supplied by two diesel electric contacts of a Steven web obviously be

The wireless station will obviously be located in the camp. Two RAMAF, type AT20M transmitters constitute the main transmitting equipment. Their coverage is 2 to 20 Mc. The final p.a. contains

four \$13s in parallel with a plate voltage of 1,600 voils supplied by the separate power supply using \$50s. The modulator power supply using \$50s. The modulator \$50s\$ to 750 wasts, fed to an inverted vee antenna (70 ft. high at the apex). Two receiving set-ip. The latter belonged to Sir Hubert Wilkins' expedition, which the properties of the properties

round either batteries or AL power to the power of the po

disposal a surgery complete with a blood transfusion unit, operating and a portable X-ray equipment. Although the main tasks of the ex-

Although the main tasks of the expedition are research, investigations to add another contribution to the great mosaic work of knowledge on Antarc-

that these volunteers, these energetic men, keer to be pioneers of the control of

Ham Radio may be listed as a means to keep these men in touch with the civilised world. Bill (ex-VK1BS in 1981) will operate under his Antarctic call sign VK1EG.

His equipment will be a modified ATS

and a Hammerlund receiver. He intends to use c.w. and also phone, if signals are strong enough,

A considerable section of the expedition's programme is headed "Held liveston's programme is headed "Held liveston's programme is the expedition of the equipment will be used. First, there are required to the expedition of the expedition of the reasons. Their excellent Antacute the French Adele Land expedition. A wessel contains special navigation inthe French Adele Land expedition. A wessel contains special navigation inbell transactive of type Sc@etG (U.S.). The frequency range is approximately tubes contitute the line-up. The set is vibrator unit. The antenna is a whip or

a long wire. Sledges hauled by huskies are the traditional snow vehicles used on Arctic and Antarctic expeditions, and thus similar sledges will be used by this expedition, too. They are also equipped the properties of the state of th traditional snow vehicles used on Arctic

nection with the wessels.
While biological, geo While biological, geological, and geophysical research and surveying carried out by the expedition will assist the completion of an over-all scientific picture of Antarctica, meteorological ob-servations taken should invaluably contribute to an improvement in this country's weather forecasting. All cold air masses reaching Australia originate at the south-polar region. So far the number of weather stations between there and here has not been and cannot be sufficient for a complete knowledge of those air masses, which, however, is vital for accurate forecasts. The estab-lishment of the new station will certainly better this position greatly, not only by adding another station, but particularly by its location very close to the origin of those cold air masses.

This article would be incomplete without a discussion of the prospects of Land. It must, however, be said that a prediction can hardly be made because not enough practical data is available Signals originating at or passing through Arctic and Antarctic regions can be affected by severe disturbances caused ionospheric and magnetic storms which are more frequent in those areas of high latitudes. In fact, the two zones of extensive auroral activity are a good indication for the expansion of these disturbed regions. A type of turbulence often exists among ionospheric layers there, causing a radio wave to be re-flected irregularly. This becomes evi-dent by a "flutter" fading, a familiar sound on signals passing through these areas, e.g. short-path contacts between Australia and the eastern part of South America (LU and PY). As a more detailed discussion would be beyond the scope of this article, we can confine our-selves to stating that MacRobertson Land may be just inside or just outside the southern auroral zone. Future will show how strong signals will be and how they will sound! After all, VK1EG is one of us, and thus however keen DXers in all corners of the globe may be to work that new DX country down south, we shall certainly be just a bit keener to contact Bill!

Special Features

The B.F.O. is switched according to the intermediate frequency and is very stable.

The Meter on the panel can be switched to check the current reading for each of the valves. In one position, it acts as a tuning indicator.

The front panel and the coil box are strong alloy discastings, other units be-ing steel or brass of heavy gauge. All metal parts are well finished and protected against rust or corrosion. Components and materials throughout are of the highest quality and the receiver is suitable for use in tropical cilmates. The Sole Australian Agents are R. H. Cunningham Pty. Ltd., of 118 Wattletree Road, Armadale, S.E.3, Vic.

Low Drift Crystals

AMATEUR BANDS

ACCURACY 0.02% OF STATED FREQUENCY

	3.5	Mc.	an	ď	7	Mc.	
Unm	oun	ted .			į	22	0
Mous	ated	e**			į	E2	10
19 =		14 2	ur.	300		¥	

Crystals, "Low Drift." Mounted only. £5.

Spot Frequency Crystals Prices on Application,

Regrinds £1 0

THESE PRICES DO NOT INCLUDE SALES TAX

MAXWELL HOWDEN

15 CLAREMONT CRES. CANTERBURY, E.7, VICTORIA

TRADE REVIEW

Eddystone "700" Communications Receiver

BRIEF SPECIFICATIONS

Frequency Coverage Ten ranges as follows, selected with a low capacity rotary switch: Range 1— 14 Mc. to 3: 3.8 , 1.5 3.8 — 1.5 ,, " —600 Kc. ", 1500 Kc. - 92

- 48 92 - 28 V1—R.F. Amplifier V2—R.F. Amplifier 6BA6 (CV454) 6BA6 (CV454) -Mixer SBES (CV453) (CV2524) V4-Oscillator 6AU6 V5—Beat Freq. Osc. V6—I.F. Amplifier V7—I.F. Amplifier BATIB (CV2524) (CV454) ARAR (CV454) 6BA6

V8—A.G.C. Amplifier SBA6 (CV454) V9—Det. & 1st Audio 6AT6 (CV452) V10-Push-Puil Driver 12AU7 (CV491) V11|Push-Puil Output 6AM5 (CV136) V13-A.G.C. Rec. & Mut. 6AL5 (CV148) V14-Voltage Stabil. VR150/30 (CV126) V15-Power Rect. 5Z4G (CV1863)

The two LF, stages operate on 465 Kc. on Ranges 1, 2, 3, 4, 5, and 7, and are switched to 110 Kc. on Ranges 6, 8, 8 and 10. Four degrees of selectivity, one

of which incorporates a crystal filter.

Input Impedance
Above 4 Mc.—72 ohms unbalanced.
Below 4 Mc.—Equivalent to a 400 pF.
capacitor in series with a 12 ohm resistor, to match into a random long wire

Output Impedance and Response

A small monitor speaker is fitted internally. On the front panel are two telephone jacks, one for the connection of an external 2.5 ohm loudspeaker, the other for telephones. Maximum output is 2.5 watts into 2.5 ohms. The response is level within 4 db from 50 to 10,000 c.p.s

Sensitivity

For a 15 db signal-to-noise ratio and 50 milliwatts output:-Above 100 Kc.-2 to 5 microvolts. Below 100 Kc.-5 to 10 microvolts.

Image Discrimination At 'least 25 db down at the highest frequency and considerably greater at other frequencies.

Automatic Gain Control The A.G.C. amplifier (V8) enables an excellent characteristic to be obtained.

The audio output varies by not more than 3 db for an increase of 80 db input, above 5 microvolts.

Power Supply

AC mains, 110 or 200/240 volts, 40/60 Total consumption 98 watts. Protecting fuses fitted.

Tuning Brive and Scale

The two-speed geared drive has reduc-tion ratios of 125 to 1 and 25 to 1 operation, being smooth and positive. The on all ranges to a high degree of accur-acy. At the top centre of the main dial is an auxiliary bandspread scale which gives an effective length of 160 inches per range. The dial is well illuminated by tubular lamps.

HAMS=

A M

We are now booking Orders for the

1954 EDITION of the

"Radio Amateurs' Handbook"

PUBLISHED BY AMERICAN RADIO RELAY LEAGUE

Price 44/3 and 2/- Postage

BOOK VOUR ORDER NOW FROM

McGILL'S Authorised Newsagency

Est. 1860 183-185 ELIZABETH STREET, MELBOURNE, C.1, VICTORIA.
"The Post Office is opposite" Phone: M 1475-7

A. & R.

QUALITY TRANSFORMERS
AND CHOKES

A. & R. EQUIPMENT

SOLD DIRECT FROM FACTORY TO YOU!

* MIOVEGOM On St. Kilds Road—lett scross from the Steme of Remembrance—the A. & R. showmoon and AND
sales department is at the service of Hamel Just Rev munited: Turn riche from the heart of the city SALES
And no parking worries for motorist! CALL, IN AND BUY YOUR TRANSFORMERS DIRECT!
Trading hours, 9 am. to 5 pm. week days only—until further notice.

MAIL ORDEE A. & R's. mail order service is geared to give fast and reliable service to Country and Interstate
SERVICE Hams. Equipment carefully packed and sent to any part of the Commonwealth.

Mounting	Primary	Secondary	DB±	C.P.S.	Watts	Typical Application	
894-23	590	2, 3.7, 8, 12.5	2	50-10,000	5	Line to Voice Coil	16/~
900-22	2,500, 5,000	2, 3,7, 8, 12.5, 15	1	*40-15,000	15	Single 807, EL34, etc., to V.C.	57/6
896-9	8,000, 10,000	2, 3.7, 8, 12.5, 15	1	30-15,000	15	P.P. 6V6Gs, A or AB1 to V.C.	62/6
897-9	8,000, 10,000	100, 125, 166, 250, 500	1	38-15,000	15	P.P. 6V6Gs, A or AB1 to Line	62/6
763-9	3,000, 5,000	2, 3.7, 8, 12.5, 15	1	40-20,000	15	P.P. 2A3s, A or AB1 to V.C.	62/6
809-26	500	2, 3,7, 8, 12-5, 15	1	\$8-20,008	15	Line to Voice Coll	42/6
870-26	10,000	2 or 8	1	*20-20,000	**6	P.P. 6V6Gs or 807s as Triodes	57/6
871-9	10,000	2 or 8	1	*20-20,000	12	P.P. 6V6Gs or 807s as Triodes	81/-
872-9	10,000	3.7 or 15	1	*20-20,000	12	P.P. 6V6Gs or 807s as Triodes	81/-
891-22	6,600	83, 100, 125, 166, 250, 500	1	50-12,000	35	P.P. 807s, AB1 to Line	82/8
892-22	3,200	50, 62, 83, 125, 250, 500	1	50-12,000	55	P.P. 807s, AB2 to Line	97/-

* NOTE

The above selection from the A. & R. standard range is available ex stock. Also Modulation and Driver Transformers. Sales Tax to be added to above prices.

Call Witis ar Telephera from the Conference of the Con

A. & R. ELECTRONIC EQUIPMENT CO. PTY. LTD.

Head Office, Factory and Sales: 378 ST. KILDA ROAD, MELBOURNE

Telegrams: "ARLEC," Melbourne. * YOU CAN RELY ON A. & R. * Telephones: MX 1150, MX 1150

FIFTY MEGACYCLES AND ABOVE

VK2WH contacted VR2CB at approx.

1025 a.m. on 30th Dec. The band re-mained open until the early afternoon and VR2CB and VR2CG were both contacted by a number of VKs mainly in the south eastern States. In due course, VR2 was heard in VK6 and vice versa: no QSO as yet but very encouraging VK2WH was the first DX contact made from Fill on 6 metres.

V.H.F. CONTEST LOGS

Please send in your log for the 1953-4 Ross A. Hull V.h.f. Contest. Don't delay, Ross A. Hull V.h.f. Contest. Don't delay, do it now! Logs to be in hands of Fed-eral Contest Committee, Box 1734, G.P.O., Sydney, not later than 24th Feb., 1954. Page 10, December issue "A.R." for rules and scoring.

NEW SOUTH WALRS

The most file of the country of the

busy 576 Mc. band is dead, but a lot of this has been given to revive it soom.

20th A.R.R.L. INTERNATIONAL DX COMPETITION

Phone: Feb. 12-14 and March 12-14 Feb. 26-28 and March 26-28

Due to lack of available space for the somewhat lengthy rules of this popular Contest, readers who desire to compete are asked to contact the Secretary in each Division who will be supplied with copies from the Federal Executive Many Australian Amateurs subscribe to "QST" and the full rules will be found in January, 1954, issue of that journal

marine at an early date, and in this regard would like to know of any activity in the Geelong area. SOUTH AUSTRALIA

There has been much activity on 60 Mc. Gar-There has been much activity on 60 Mc. Gar-have said off with some very good DV with have said off with some very good DV with the control of the control of the con-set the same time as the 6 pm contact. It has the control of the control of the con-set the same time as the 6 pm contact. It has at the same time as the 6 pm contact. It has the change of the control of the con-tact of the con-tact of the control of the con-tact of the con-tact of the con-trol of the con-of the con-trol of the con-of the con-trol of the con-trol of the con-trol of the con-of the con-of

operation were generated of name for which control to the control of the control

Has anyone used their 6 mx beam for 2 mx work yet—if not why not? I'll tell you later if it works, because I have just repaired mine after the storm!—GAU.

USE VOICE OPERATED CONTROL GLORAD PLUG-IN HNET TYPE 2161



supplied with external 3,000 type relay equipped with H.D. contacts ready to mount in the transmitter is ideal for the job.

WRITE OR PHONE FOR DETAILS

CLORAD ENGINEERING SERVICES

291a TOORONGA ROAD, MALVERN, S.E.S. VIC. Phone: UY 3974



STILL YOUR BEST FRIEND AND SUPPLIER OF .

ALL RADIO COMPONENTS

AT THE LOWEST PRICES

Continue to avail yourself of our Showroom self-service system or mail order facilities.

J.H. MAGRATHEC. PTY.

208 LITTLE LONSDALE STREET, MELBOURNE, VIC.

Phone: FB 3731

MARINE TYPE MRT12 TRANSCEIVER

Designed for Small Ship operation. May also be used for Amateur Bushfire Work, etc. Very reasonably priced. Full Minited Bushine work, etc.
Very reasonably priced. Full
details and descriptive leafiet
from Firms handling Bright Star Crystals or direct.

Limited number Taylor Tubes: TZ20s, £2/10/- each; TR35s, £6/10/- each.

Transmitters altered for Bush Fire and Fishing Boat Work. CRYSTALS, as illustrated, 40 or 80 mx, AT or BT cut. Accuracy 0.02% of your specified frequency, £2/12/6 each.



20 metre Zero Drift £5 each. Large, 40 or 80

mx unmouted, £2 each Special and Commercial Crystals-Prices on application.

BRIGHT STAR CRESTALS may be obtained from the following interstate firms Mesur A. E. Harrold, 133 Charlotte St. Birbane, Grynef & Goodnan Lid., 137-158 Runnie St. Adelnick, A. G. Helling Lid., 151 F. Harrold, 133 Charlotte, A. G. Helling Lid., 151 F. Harrold, 133 Charlotte, A. G. Helling Lid., 151 F. Harrold, 133 Charlotte, A. G. Helling Lid., 151 F. Harrold, 133 Charlotte, 151 F. Harrold, 151 F DC11 TYPE CRYSTAL HOLDERS WANTED. ANY QUANTITY

Screw-type Neutralising Condens. (National type), suits all triode tubes, polystyrene insulation, 19/6 ea 46 EASTGATE ST., OAKLEIGH, S.E.12, VIC. Phone: UM 3387 Prompt delivery on all Country and Interstate Orders. Satisfaction Guaranteed.



Crystals re-ground, £1 each

DX ACTIVITY BY VK3AHH

BY HIGHLIGHTS

All who missed CEBAA a few months ago will have another chance to work Easter Island CEOAC (phone) and CEOAD (c.w. and phone) expect to commence operation on the 20th January. Let us hope that more than seven VKs are lucky this time! (thanks 3CX).

There is hope for new activity from Niue Island. Probable call sign is ZK2AC (thanks BERS195).

All being well, Bill Storer, VK1EG (cx-1BS, 2EG), wireless operator of the expedition to Antarctica, should begin operation towards the end of February.

BAND CONDITIONS

operation towards the end of Pebruary.

2. S.A. DO CONDITIONS

2. S.

a number of sections 1900-1700-1700 and was been mently over an a rule got very reliable to mently over a rule got very reliable to the rule got very less than 1900 and the Province and 1900 a Lin BANJ reports VQ4DV- FASVN- 6XPQ-and FURAD- Up in Queensiand. Bob 8RW keyed with TizTG- ZS- FQ8AK- CR8At-E14Q- LUSAG- STSAR- F78AD- Y1ZAM-CESAD- KV4DB- FTENG- LE- 4XJ managed JZ0KF- F18AR- VR4AE- XZ2OM-ZC4FE-VSIFX-, and FORAC XW8AA. Rob 3EG menCont. 2007 . WAY TOTAL T

CHIEF OF THE PARTY CONSER. SPHENEY, CONTROL SPHENEY, CONT

XZIKN

71 Me As usual, this band displayed erratic conditions to all continents. American openings were likely between 2200 and 6000s and sometimes Europe came through around 9900-1100s with Africa from about 4500 to 1000s.

with Africe from about 1000 to 1000.

15.88 worked VSIES. DUSTS and Queetin.

15.81 worked VSIES. EXEST. AGARC.

15.81 WORLD VSIES. EXASC.

25.82 WORLD VSIES. EXASC.

25.82 WORLD VSIES. EXASC.

25.82 WORLD VSIES.

25.83 WORLD VSIES.

25.83 WORLD VSIES.

25.84 WORLD

European ZCHRX
EN Scandard State Control of the Con

GENERAL NEWS

GENERAL NEWS

On the 4th January, the Rista Da. expedition ship of the Astronta Division of the Dept. the Astronomy of the Control of the Con

well known by now, Bill Storer, VKIEG, is a wireless operator of the expedition It is hoped that after a successful innding of the team propagation conditions will be kind to us an allow communication. Whatever the case, Bill these after a successful introduce of the team, and assists communication. Whetever the team, Mill. and the communication was been as the communication of t

The of linear THE CONTROLLED AND THE OFTEN A

Me.). My thanks this month go to VKs 1AC, 2QL, 2AHR, TAMB, ZAOU, SCK, ZIM, 3JJ, 3PA, 3TF, 3UR, 3XB, 3YS, 3ALQ, SANJ, 3ATN, 3AXR, 4RW, 4RT, 4TN, 6XJ, SUW, 5RG, 5WG, 5WG, 6RK, 6KE, 6EU, 7DZ, 5VY, and to awdia BERSISE (VKS), Norman Clarks (VKS), Dick Jenkin (VKS), and Dave Jenkin (VKS), Dick Jenkin (VKS), and Dave Jenkin (VKS).



FEDERAL, QSL, and



DIVISIONAL NOTES

FEDERAL

RADIO AMATRIE CALL SION BOOK
Work has proressed very authoritorily with
Work has proressed very authoritorily with
sleave Call Block and it is hoped that this well
be recorded to the control of the control
be recorded to the control of the control
be reported a most ascentility to 5 byther after
reported a most ascentility to 5 byther after
made that mere devertising will be available
to the control of the control
be reported to the control
be repor EADIO AMATEUR CALL SIGN BOOK

now, in order with your Lividical Societary Kord Renember II you have any doubts as to the accuracy of your eddress on the filse of the Pointsafer-General's Department let us have a correction without delay. If you change your GH begin and the point of the pointsafe of the poin

RAN TO ESPAND FEDERAL EXECUTIVE
Rice; the west the Wireless finitive of Americals are given in every flate and the Dirtrails has given in every flate and the Dirceptor of the Committee of the Committee of the Committee of the Committee of the Individual Committee of Individual

NATIONAL FIELD DAY CONTEST

ALL BANDS ON SUNDAY, 14th FEBRUARY, 1954

See "A.R." page 10 of the January issue for details. Write to-day to the Wireless Inspector in State for your PORTABLE PERMIT

Fixed or Home Stations, do not forget there is a section for you, too. Certificates will be awarded to the top scorers in the various sections in each State.

FEDERAL QSL BUREAU RAY JONES, VKIRJ, MANAGER

EAT JONES, VIKELJ, MANAGER
The results of the All European DX Contest
1902, staged by the Dunish Radio Society as part of their invest plates (collectivations, are not of their since plates (collectivation), are not of their plates of the There raise have been issued by the EDA. There raise have been issued by the EDA proved to difficult for non-Encodesseins constitute to complete with not beauty modifications of the encodessein to complete the encodessein to complete the encodessein the

information is included in the book quite a few Hans were included among the 500 people who gethered at 5 North Wharf or 500 people who gethered at 5 North Wharf or 500 people who gethered at 5 North Wharf or 500 people with a second to 100 people with the second the secon

VELISM, VIE VERNIS, DICK VERNIS and Source. Pred Cropley, ZILAMI, complete with XTL, and seven, repeat seven, sons, resently arrived previous city. A wise choice Free and welcome to you still.

It was not been a seven of the control of the contro

The transitive and the second of the second

NEW SOUTH WALES

The last meeting of this Division was the hotstmas Social which was held at the usus setting place and was attended by approximately 70 members. About the only business on the Constitution.

Coloured sildes were shown by Ken 2AXZ
and the Secretary Dud 21Q covering a variety
of scenes from Norfolk and Lord Hone Misends,
last year's Zene Convention at Urunga, Wen
ragamba Dam, and Southern Tablelands of VK2.
Last, but not lesst, in the boys' estimation,
the convention of the Convention

The Division had a visit from a Magarine committee member in Ron 3RN. A few dissaints were held at the Pharmacy and one in the electrical department of a well known armiture store in the city.

DESCRIPTION OF THE PERSON NAMED IN

All's quiet on the Western Front Is an old styling, but It is still true for Ham Badlo styling, but I'll is still true for Ham Badlo Annandake on 21 Mc, but Aloff speeze for have given it swey for westing a check akirt with the still silence is facilitied in Strukheide, good to hear programmer. The programmer of the

HUNTER BRANCH

The main event for the man our Hauter Branch Carles of the Manual Franch Carles of the



personally-phone your order -or write to U.R.D. for your Goodmans ENTIRE RADIO and ELEC-

> Licensed amateurs! We have the vesy equipment and components you want!

to cultivate your confidence! Remember - Open daily, 8.30 a.m.-5.00 p.m. and Saturday mornings, 8.30-11.30 a.m. Make it a date, eh?

PICHT IN THE HEART OF THE CITY -

vet you can park for those precious few minutes! UNITED RADIO DISTRIBUTORS PTY, LTD.

Radio Electric Wholesalers SHOWROOMS: 173 Phillip St., SYDNEY -- OFFICES: 183 Pitt St., SYDNEY

Telegrams: URD Sydney - Phone 8L 3954 (3 lines) 5789A

Page 16

Urunga Convention

The usual North Coast and Tablelands Convention is to be held at Urunga again this Easter. Make your plans now.

Committee is under the chair-manship of Zone Officer, Noel Hansen, 2AHH

Hansen, ZAHH Interstate visitors are requested to make their arrangements early by contacting 2AHH, 2XO, or any of the North Coast gang for full

It is too well known in VE2 and VK3 to warrant further comment.

The Christians Trye, which had pride of place of the control little, describes and years and years and years and years and years and years and years and years for first and Makison Discose concluded accident for the control of the control o worked Total NACE, and News, 24NO in Springer Problems and Subre 1 and 5 During the control of t

The next meeting of the Hunter Branch will be held at Tighes Hill Technical College at 8 p.m. on 12th February, 1854.

CANBERRA RADIO CLUB

CANBERRA ANDIO CLUB
The above chib had its second Annual flocial
formed spent as enjoyable evening in the chivment. It has report as enjoyable evening in the chib
the positions of Hen. Secretary and Transace
the positions of Hen. Secretary and Transace
secretary. The chib it is now index reconsecretary ones to be a secretary and the secretary
and the secretary and the secretary and the secretary
to the secretary and the secretary and the secretary. The chib it is now index reconsecretary. The chib it is formed to be secretary the secretary of the secretary and the secretary a

VICTORIA

Bulletin State for the sensite a rules a problem. We metale, so Tre State and problem. We metale, so Tre State and so problem. We metale, so Tre State and so problem. We metale a sensite and the sensite and

TRANSMITTER HUNT, 28th FEBRUARY Details of the proposed marathon hunt has now been discussed and this hunt is schedule for Sunday, 38th Pebruary. There will be for the to the live second to be bested at a southern assistant as a furnishing location. It is bosed to award prizes, one for the winner and one of the winner and one of the live second to award prizes, one for the winner and the live second to the control of the live second to the

being deducted.

Assembly parts is at College Parts, rest parts, rest parts in a college Parts, rest parts, rest parts in a college Parts, rest parts, rest parts in a college Parts, rest par 2825 Kc. with cell sign of VKLAPC.
It is expected that a member of the press
It is expected that of the press
photographer, so we sak you to come along
bright and early, compellors and nonbright expected to the come along
west your Institute badge! Bring your handwest your Institute badge! Bring your handwest your English as map of appositead tos, if required, plass a map of appositthe family, fell your friends to come along—
the more the merrier!

Non-competitors who are unable to join in at the commencement, may assemble in College Parade at 2 to 3.00 p.m. and will be given directions from there.

NORTH EASTERN ZONE
It is reported but Murray SIGN was not able
to reported but Murray SIGN was not able
to the second process of the second process
at the leading total on the local CWA must
be second process. The second process of the second process
and the second process of the second process
pulpaged on the activities of Alex SIGN. Pater
pulpaged on the activities of Alex SIGN. Pater
pulpaged on the activities of Alex SIGN. Pater
pulpaged on the activities of Alex SIGN.
The second pulpaged that the time was well
as the second process of the process
contact on 6 ms when has based of and also
contact on 6 ms when has based of and also
contact on 6 ms when has based of and also
contact of 6 ms when has based of and also
contact of 6 ms when has based of and also
contact of 6 ms when has based of and also
contact of 6 ms when has based of a contact of 6 ms
and of 6 ms when has based of 6 ms when has based on the second process
and the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has based on the second process of 6 ms when has been had been

have a voint from Doug Hz a write book.

The list some blooken Drevensky have very real to be a very r

properior eway fishing if he makes it too too the OM. He meets the public eye, Associate Vern Wyatt and a mate, Lex, will have at for their A.O.C.P. exam, and we all hope the questions were the ones they knew the answer except the control of the

CESSATION OF A.F. TRANSMISSIONS

It is regretted that the A.F.T.

Transmissions from VKJWI will have to be cancelled for the time being. When it is possible to re-commence this service full in-formation will be contained in "Amateur Radio."

Zone activities were at a low level during the holiday period although the zone hosb-to-book of the control of

bush fire rich.

""" stilling beats during the sumper 1502 Charging 558 and bits and pieces.

Docks like 144 Mc. again, what about it AdaKI.

And the 144 Mc. again, what about it AdaKI.

And the 144 Mc. again, what about it AdaKI.

And the 144 Mc. again, what about it AdaKI.

And the 144 Mc. again, what a sum of the 144 Mc.

A discussion on the proposed cutting up of the some using the regional boundaries has means this sume would be set in that a less three parts, leaving three or four active Manus in at season the sum of the sum of the 144 Mc.

Bester 1514 a spice be cut if from the estating the sum of the 144 Mc.

Bester 1514 a spice be cut if from the estating the sum of the 144 Mc.

Bester 1514 a spice be cut if from the estating the sum of the 144 Mc.

On Wednesday, 8th January, the Annual Company, 19 Marian Company, 19 Marian Company, 19 Marian Carlotte Carlotte Company, 19 Marian Carlotte Company, 19 Marian Carlotte Carlotte Company, 19 Marian Carlotte Carlotte Company, 19 Marian Carlotte Ca

Chas STI, who with Fred attended the Benelis Convention, gave us a very comprehensive report on the Convention and several items on the agends paper were discussed fully The meeting concluded with supper provided by MMP's XII. Bill and Charife brought some two mx equipment, which was inspected with great interest by the members. A practical

femonstration was given by Chas and Bill I rove that the gear worked. Chas operated in x at his home and it was received on Bill was received in the second of the second of the work of the second of the second of the second or 2 mx. Bill 3ATU has a sked with the gas if Remark in S.A. and has hopes of bridgin spe to have more news of the 2 mx activities went mosts.

GELOVI AMATRIE RADO CLUB
The module of December was an active on
eithers, the questions being AMX and 2MX
for the best of the property of the control of the control
among the control of the control of the control
among the control of the control of the control
among the control of the control of the control
among the control of the control of the control
among the control of the control of the control
among the control of the control of the control
among the control of the control of the control
among the contr

QUEENSLAND

attendance Hope one resolution you make will be to sitend your meetings more regularly it 1864. Two very interesting lectures were given one by John 4FT on "Balanced Bridge VT V.Ms." and the other by Tom Athey on "Molching Transmisson Lines"—both abby presented and enlightening.

The Dutch specion wann't so guccestful as

having any money. The hearing side were balloted for and among the luxby once were 477. John 437 har converted his to the second of the local part of the second his to were good results, though he sort having much tack with the crystal leaser as a mile, looks as Arthur 4AW filled the breach and organized the Xmas Do, which was well attended by strange to say, quite a few who we haven't ambier laquid, and the jokes—blue and otherwise—and he overgone criving the local parts.

in Britchen and a usual getting behind in Dividen with his usual activity. Front organ parent behind the behin

The state of the s

GERARD & GOODMAN LIMITED —

Phone: W 1541 (8 lines)

192-196 RUNDLE STREET, ADELAIDE, S.A.

Our Radio Department gives YOU the Service . . .

Telegrams: "GANDG," ADELAIDE

ARE YOU LOOKING FOR THESE? WE STOCK THEM!

PAINTON CONNECTORS

2 way to 33 way. Detailed description of types on request.

TELETRON ST59L/2 SOCKET

with shield (mica filled 9-pin for 12AT7, etc.)-10/6 each.

4 GANG TUNING CONDENSER

550 pF. max. Ceramic insulation, 4" shaft-42/6 each.

XFG1 VALVES Model Aircraft control-33/-.

Model Aircraft control-33/

3A5 VALVES

Model Aircraft control-26/-

GANGED POTENTIOMETERS

First gang-13/6; extra sections (up to 4)-12/6 per section.

WATWEE

V /A.1	4 9	M/S				
12AT7						32/6
12AU7	***	***		****	****	24/3
12AX7	****	4+44	****	++<+	44.60	26/3
EF86	****					30/6
RL16	(400)	Mc.	Tri	ode)		15/-
CV66	(Gro	ound	ed (Grid) .	15/-

CHASSIS & COVER

for six valve amplifier — 95/-

COAX CABLE

80 ohm—1/11 vard

CIRCLE CUTTERS

1" to 3\["-20/9 each

aucers, seems to and ume to play with h.B.f.s. ind f.s.R.c. or something.

Harry 40X (Mackay) put a very nice sign.

Brisbane during Kmas. I believe he in the new first sellive up there with an occasional bur from 40Q.

This Rockly boys came through one evening contraction of the contract of the

New York, John Sie's in his sourced an extraction of the control o

SOUTH AUSTRALIA

when the control of t

that the interfacement place of the second controlled and Next Meanura, a member of the second controlled and Next Meanura, a member of the second controlled and the second c

The second secon

UPPER MURRAY AREAS

The December method of the Upper Many New York (1997) and the Common of the Upper Many New York (1997) and the Upper Many

and a certain Ham from that area was a entrain. Riding down the road on Ratilla Salvation." he came to a small fire burnition the side of the track and proceeded to diorder that the salvation of the salvation of a man who told kin not to bother as it was part of the test and he had accored full poin for that part of the test. Mounting his most consulty recordations a few rooms tests, he assecessfully recordations a few rooms tests, he assegarden. Healthy dimonnthing be again rushed income and the lacking the rushibin around a more had the factoring the rushibin around a more had the factoring the rushibing the rushibing

we this month and not "I are it is not all your war. Due 1007, lines 100, Gooden 5XX or were Due 1007, lines 100, Gooden 5XX or were Due 1007, lines 100, lines 100,

Ad Acas thes previous to this year. In several was several to the several was a series of the several was a series of the several was a severa

I ask!!

SCH has started to build his new shack, which a move in the right direction. Claude has sen heard on the v.h.f. frequencies and also se emergency fire service frequencies. STW has as a few contacts on 20 mx and also manager

there is no conformation of this as yet, although waters with the Conformation of the art water waters with the Conformation of the Conformation o

poils Martin And a couple of POOIS POOISS To They all support when I at them I a directly of Pools and the Pools a

for the coming year, I salute you. titler but my littering mechanism overtime! I desire to thank Norm C planting the idea of the v.h.fr. in Charlie SON for presenting me with tx, and Rex SEX for so manfully co to my heatisant and feeble plea for on 288 Mc. Good heaven! Did I do toward winning the Contest? As I s "They all laughed. etc., etc." You.

WESTERN AUSTRALIA

TASMANIA

control and all.
The exhibit has sitracted large crowds so far, specially when the band is open and contact and co

HAMADS

9d. per line, minimum 2/-. Pd. per line, millimilin 7/-.
Advertiseness under this heading will only be accepted from limitute Members who desire it dispose of equipment which is thair own personal property. Copy must be received by fit advertiseness. Calculation of cost is based on an average of six words a line. Desires advertiseness not accepted in this column.

corder deck, fast forward, etc., 260 or best offer. Also AR7 Receiver, 500 Kc. to 32 Mc. Wanted to buy or exchange above for good Communication Receiver, band switched (not AR7 type). Werownbill, 71 Gheringhap St., Geelong, Vic.; Phone 5674. FOR SALE .- Soundmirror Tape Re-

MUST QIT. going Oversear. Selling MUST QIT. going Oversear. Selling Model 150 Receiver with marching speaker and phopes, almost new 100 watt Rig complete on Eddystone rack 50 watta. Prefer sell complete, but might part. Also Army 22 transceiver complete. Large quantity parts. Avo-from Witte Box 10, Rockies Essi, Erisbane, S.5.

OFFER wanted, complete 3 el. rotary beam 14 Mc.) including selayar motors, in the control of the

SELL.-Ham Radio parts: Power Sup-SELL.—Ham Radio parts: Power Sup-plies 200 Ms. mains and m/g; Leach Relays, and others; Meters, Condensers, etc.; 5" C.R.O. parts. Must sell, best offer part or lot. Apply 13 Rutland Ave., Brighton, South Aust.

SELL.—4 G.E. Tuning Units (£8); 1 R.C.A. 100 Kc. Crystal (£2); 10 Xtals various frequencies (£5); 1 BC733D Receiver less crystals (£5); 1 Command Recoiver 6-9.1 Mc. (£4); 1 Tommand Xmitter; 5.3-7 Mc. (£4); 1 TA12D Xmitter (£10); 1 AR sonverted to AC Xmitter (£10); 1 AHS converted to AC with 8 inch speaker and power supply (£20); 1 ATS Aerial Coupler (£3); all apparatus complete with tubes; 1 Command Xmitter Aerial Relay Unit (£1). £60 the lot (will separate), J. W. Nairo, 22 McLean St., Morwell, Vic.

WANTED TO BUY.—Copy "CQ" Feb., 1953. Bail, 60 Shannon St., Box Hill, Vic. WX 2213.

WANTED TO SELL: Eddystone "750" Receiver, complete with 100 Kc. in-built Crystal Calibrator. In perfect order. Write "750," c/o. 384 Glenferrie Road, Malvern, Vic.

Homecrafts * RADIO * BARGAINS

NEW TAPE DECK



- Weight 74 lbs.
- High fidelity 50 to 9,000 c.p.s. One hour playing for each spool.
- Self-contained motor. Electronic erase head fitted. * Built-in vernier control. * Fast forward and re-wind.

Price complete £40 Plus 121/2 per cent. Sales Tax.

MODEL 150 PICK-UP World famous Goldring Model 150 Pck-up, Brand new with two sapphires for standard or microgroove recordings Reduced from £7/16/6 to 39/6. Limited





KARSET KIT

Car Radio Kit, as described in "Radio & Hobbies," March, 1952, issue. Karset complete to the last nut and bolt, including 6 inch Rola Speaker, 22 Gns. Also 1953 model, as illustrated in "Radio & Hobbies," April, 1953, 28 Gns.

BARGAIN KEROSENE STOVES



Latest type. No pressure required, absolutely safe. Boils kettle of water in 12 minutes. Price only 59/6.

CONVERT YOUR EXISTING 78 R.P.M. RECORD PLAYER TO "MICROGROOVE"



Easy to install. Pick-up has interchangeable heads. Cantilever type response. Even speed reduction.

Price as illustrated £6/19/6

Q-PLUS OSCILLATOR



Outstanding Value With Modulated 455 Kc. Note accurate I.F. alignment.

VALVE BARGAINS

BKTG				7/1
1J6				7/1
1H6				3/1
6H6				7/1
6A6				7/1
1H4				3/1
76				7/1
A630				2/1



ALL-PURPOSE TEST MULTIMETER 1,800 ohms per 200,000 elf con

plus 12% S.T.

COUNTRY AND INTERSTATE CLIENTS PLEASE ADD FREIGHT OR POSTAGE.

STOP PRESS BARGAINS

- * 12v, 500 watt Generators 99/6 * 100 Ma. 30 Henry Chokes 12/11 * 913 Cathode Ray Tubes 39/6 * Five-Pole W/Switch 6/11 * 0-20 volt Meters ______ 14/11 * Aluminium Chassis from 5/16. Large
- variety to choose from. * Pick-ups for long playing or standard Records 59/6
- * New 954 and 955 Valves 7/11 * Amplifier Cabinets, 10-watt size, 55/-
- * Amplifier Cabinets 25-watt size 69/6



* BARGAIN *

Electric Gramo Unit, 78 r.p.m. 230 volt synchronous Turntable with High Fidelity Magnetic Pick-up. Automatic Stop. Cut to only 84/-

> + BARGAIN + Bakelite Mantel Cabinets-4/11 each

SPEAKER BARGAIN FAMOUS MAKE

High Fidelity well known English make Twin-Cone 12 inch diameter 15 watt Speaker, £17/17/-.

FB 3711



A FINE BRITISH MADE COMMUNICATIONS RECEIVER OF ADVANCED DESIGN AND FIRST-CLASS CONSTRUCTION

The new Eddystone "750" Receiver employs the latest technique in double superheterodyne circuits and combines high selectivity and sensitivity with excellent signal-to-noise ratio.

CIRCUIT

The receiver is an eleven valve double superheterodyne including one R.F. Amplifying Stage.

BANDSPREAD

The ingenious mechanical bandspread mechanism gives an almost linear scale equivalent to about 32 feet on each tuning range. The figures that follow apply to bandspread coverage on the bands allocated to Amateurs at the Atlantic City Conference. Variation in the width of each Amateur band necessarily affects the degree of coverage and against each band we have shown the number of vernier divisions required to tune over the corresponding number of killocycles for each separate band width.

	Band Width				Tuning Coverage on Vernier Scale	Vernier Divisions of Band- spread	Kilo- cycles in Band
21.45	Mc. Mc. Mc. Mc. Mc. Mc.	to to to to to		Mc. Mc. Mc. Mc. Mc. Mc. Mc.	34.375" 7.5" 6.45" 15" 61" 30"	208 45.5 39 91 364 182	1700 450 350 300 500 200

TUNING RANGE

The receiver is provided with four wave bands, the first three overlapping and covering from 32 to 1.7 Mc. and the fourth covering 1465 to 480 Kc. Each band is selected by a low capacity switch. The

actual ranges are:
(1) 32 Mc. to 12 Mc.
(2) 12 Mc. to 4.5 Mc.
(3) 4.5 Mc. to 1.7 Mc.
(4) 1465 Kc. to 480 Kc.

"S" METER

A socket is fitted at the rear of the receiver, into which an external "S" Meter Unit—Cat. No. 689—can be connected.

INTERMEDIATE FREQUENCY STAGES

The first LF is 1620 Kc. and the second 85 Kc. This combination results in high adjacent channel selectivity and negligible image interference. The transformers are robustly constructed and permeability tuned.

DISTRIBUTED BY:

Western Aus.: Carlyle & Co. Ltd.
Atkins (W.A.) Ltd.
Victoria: William Willia & Co.
N.S.W.: John Martin Fry. Ltd.
Derendand: Chandler Fry. Ltd.
Noves Rese. Ltd.
Noves Rese. Ltd.

Sole Australian Factory Representatives:

R.H.CUNNINGHAM PTY. LTD.

118 WATTLETEE RD., ARMADALE, Vic. Tel. UY 6274, Cable "Connig" Melbourne.

3 CAMBRIDGE ROAD, DRUMMOYNE, Tel. WA 1015, Cable "Cunnig" Sydney.